

DESCRIPTION	ELECTRIC 30" WIDE OVENS	
	RVSOE330	RVDOE330
Overall Width	29 3/4" (75.6 cm)	
Overall Height	29 3/8" (74.6 cm)	51 3/8" (130.5 cm)
Overall Depth	To front of door – 25 3/16" (64.3 cm)	
Cutout Width	Standard – 28 1/2" (72.4 cm) Flush mount* – 29 5/8" (75.2 cm)	
Cutout Height	Standard – 28 1/4" (71.8 cm) Flush mount* – 29 1/2" (74.9 cm)	Standard – 50 5/8" (128.6 cm) Flush mount* – 51 1/2" (130.8 cm)
Cutout Depth	Standard – 24" (61.0 cm) Flush mount* – 25 1/4" (64.1 cm)	
Electrical Requirements	4-wire ground, 240VAC, 30-amp electrical connection for single oven/50-amp for double oven. Unit is equipped with No. 10 ground wire conduit. Should be fused separately.	
Maximum Amp Usage	240V – 23.3 amps 208V – 20.2 amps	240V – 46.7 amps 208V – 40.5 amps
Oven Interior Width	25" (63.5 cm)	
Oven Interior Height	16" (40.6 cm)	
Oven Interior Depth	18 1/2" (50.0 cm)	
Oven Volume	Overall – 4.3 cu. ft. AHAM** – 3.8 cu. ft.	
Approximate Shipping Weight	259 lb. (117.6 kg)	374 lb. (174.2 kg)

* To install the oven in a flush mount application, the flush mount accessory kit (D30FTS for single oven and D30FTD for double ovens) is required.

**The AHAM standard for measuring oven capacity subtracts the doorplug and convection baffle dimension from the total oven volume.



Viking Range, LLC | 1-888-845-4641 or 662-455-1200

For detailed product information, model numbers, or to request a quote visit vikingrange.com

© 2013 Viking Range, LLC | Specifications subject to change without notice.