# 1024BEV

24" Beverage Center • 1000 Series





# **FEATURES & BENEFITS**

PERFORMANCE	<ul> <li>Overall volume of 5.4 cu ft holds up to 85 bottles (12 oz) or 105 cans (12 oz) and 16 wine bottles (750 ml)</li> <li>Mechanical Dial Control is conveniently located on the grille</li> <li>Approximate temperature range: 34°F - 45°F</li> <li>Passive cooling system</li> </ul>
INTERIOR/EXTERIOR	<ul> <li>White interior is illuminated with recessed incandescent lighting that automatically turns off when the door is closed</li> <li>Three-quarter extension zinc coated wine racks allow for easy access</li> <li>Wine racks accommodate a variety of bottle shapes and sizes</li> <li>Two adjustable tempered glass shelves</li> <li>LowE coated, argon gas filled, dual thermopane glass door provides protection from harmful UV light</li> <li>Stainless steel handle (7/s" diameter)</li> <li>Door swing is field reversible, and is shipped right-hand hinged</li> </ul>
INTEGRATION	<ul> <li>Unit is designed to be built-in or can be freestanding with the freestanding accessory kit</li> <li>Solid natural beech wood fronts on wine racks can easily be stained to match surrounding cabinetry</li> <li>Four independently adjustable levelling legs provide a precise undercounter fit</li> </ul>

### **MODEL DETAILS**

STAINLESS FRAME

Model	Voltage/Hz	Door Swing	Finish	Shipping Weight
U-1024BEVS-00B	115 / 60	Field Reversible Door	Stainless Frame	126 lb


## ACCESSORIES

Model	Description	Finish	Shipping Weight
ULAFREESTANDB	Freestanding Kit	Black	3 lb


**1024BEV** 

1000 Series • 24" Beverage Center

#### DIMENSIONS



## **CABINET CUT-OUT**



#### **INSTALLATION NOTES**

When installing adjacent to wall, ensure 2  $\frac{1}{2}$ " clearance on hinged side for 90° door opening, allowing ample room for door handle.

Cutout includes the additional  $\frac{1}{4}$  width overall to ensure proper installation.

No additional clearance around sides, top or rear of unit is needed for ventilation.

Do not obstruct front grille air flow.

#### SPECIFICATIONS

Model	1024BEV
Amps: Running	1.2
Capacity: Bottle (12 oz)	85
Capacity: Can (12 oz)	105
Capacity: Volume (cu ft)	5.4
Capacity: Wine Bottle (750 ml)	16
Control Type	Mechanical Dial
Dimensions: Product Depth	23 ¼" / 591 mm
Dimensions: Product Height	34 1⁄8" / 867 mm
Dimensions: Product Width	24" / 610 mm
Energy Consumption: Avg. Per Year	305 kWh
ENERGY STAR	No
Product Weight: Max	116 lb
Refrigerant Type	R600a
Sabbath (Star K Certified)	No
Temperature Range	34°F - 45°F

#### **COOLING SYSTEM**



## **ELECTRICAL REQUIREMENTS**

This unit requires a grounded, polarized 115 VAC, 60 Hz, 15 A power supply (normal household current).



Please visit u-line.com to view this model's User Guide & Service Manual. All Specifications are subject to change without notice.