



Page 1 of 2






Kenmore Elite 25 cu. ft. Bottom Freezer Refrigerator



O White 46-71032

- O Stainless 46-71033
- Ultra Satin 46-71036
- Black 46-71039
- New 25 cu. ft. capacity in a 33" wide cabinet
- Multi Air Flow cooling system
- Tall, integrated through-the-door dispenser with light and Ultra Ice®
- Blue LED night light with sensor
- GeniusCool™ Technology
- Full-width, temperature-controlled gourmet pantry drawer
- 2 humidity-controlled crispers
- 5 glass shelves
- 7 door storage bins
- · Slim In-Door icemaker
- Pull-out freezer drawer
- Exterior electronic temperature controls with digital display
- · LED lighting in fresh food and freezer compartment
- Factory-installed icemaker
- · Contoured, smooth doors with hidden hinges and aluminum handles
- 32 7/8" W x 69 1/8" H x 35" D



- A Height without Hinge
- D Depth with Handle
- B Height with Hinge
- E Max. Depth with Doors / Drawer Open
- $C- \text{Depth without Handle} \hspace{0.5cm} \textbf{F}- \text{Width}$
- Clearance Additional Width Required to Open the Doors 90°

Left Hinge – Facing the refrigerator, handle is on your right and hinges are on your left. Right Hinge - Facing the refrigerator, handle is on your left and hinges are on your right.

Dimensions.	Height		Depth			Width	Clearances	
Inches	Α	В	С	D	E	F	Door Edge	Handle
46-7103X	67 7/8	69 1/8	32 1/2	35	46 3/64	32 7/8	4 1/2	7

MINIMUM OPENING REQUIRED: When installing next to cabinets, add Width (F) and Door Edge Clearance. When installing next to a wall, add Width (F) and Handle Clearance.

SELECTION	ELITE		
FACTORY ICE			
White	46-71032		
Stainless	46-71033		
Ultra Satin™	46-71036		
Black	46-71039		
INTERIOR CAPACITIES			
Total Volume (cu. ft.)	25.0		
Refrigerator / Freezer Volume (cu. ft.)	17.5 / 7.5		
REFRIGERATION FEATURES			
GeniusCool™ Technology			
Multi Air Flow System			
Total Interior Glass Shelves	5 (4 Adjustable)		
Spill Proof Shelves	4		
Slide-Out Shelves	4		
Split Shelves	4		
Full-Width Gourmet Pantry Drawer	1 TempControlled		
Humidity-Controlled Crisper	2 Clear		
Total Door Shelves / Bins	7 (2 Adjustable)		
Gallon Door Storage	2		
Covered Dairy Bin	•		
Refrigerator Light(s)	LED		
WATER FILTRATION AND DISPENSER	LES		
Water Filtration System	NSF® Certified		
Water Filter Change Indicator	Exterior		
Water Filter Location	Interior		
Water Filter Replacement [†]	46-9690		
water ritter neplacement.	Tall. Integrated with		
Through-the-Door Dispenser with Light	IntelliTouch Controls		
Express Fill Technology	•		
Type of Ice	Cubed / Crushed		
Dispenser Control Lockout	•		
Night Light	Blue LED w/Sensor		
Dispenser Light	•		
FREEZER FEATURES			
Drawer / Door Type	Pull-Out		
Factory-Installed Icemaker (Ice)	Slim In-Door		
Removable Ice Caddie	•		
Fast Ice Production*	Ultra Ice®		
Freezer Light(s)	LED		
	2 Full-Width, Slide-Out		
Freezer Organization	Removable Baskets		
GENERAL FEATURES			
	Electronic Up-Front wit		
Temperature Controls	Digital Display		
Door Style / Finish	Contoured, Smooth Doo		
Color-Matched Cabinet / Hinge	•		
Hidden Hinges	•		
Door Handle Finish	Aluminum		
Door Alarm	•		
ENERGY STAR® Qualified	•		
Est. Energy Consumption (kWh / yr.)	551		
Est. Yearly Operating Cost**	\$59		
Volts / Amps	120 / 15		
Shipping Weight (Approx. Lbs.)	308		
WARRANTY			
1-Year Limited Warranty -	Parts & Labor		
Entire Appliance†	Paris & Labor		
	Parts & Labor Parts & Labor		







If used for other than private family purposes, warranty applies for only 90 days.

"Increases ice production by 20% in 24 hours long large cost of \$0.1065 / kWh.

"All energy \$ / Yr. figures are calculated at the national average cost of \$0.1065 / kWh.

Energy rehates are offered and paid by the energy supplier in states where such programs exist. Criterion is based on percentage of energy efficiency attained beyond the 2007 standard. Dollar amounts may differ †Excludes water filter



Page 2 of 2

MEASURE TWICE...ORDER ONCE

Step-by-Step Instructions to Assure You Order the Proper Size Refrigerator

It's Just Good Measure To Double Check Before You Order!

- 1. Measure the opening for the refrigerator. Don't forget baseboards, molding, tile, countertop overhang, etc. If there is an island in your kitchen, be sure there is enough room to open the door.
- 2. Refer to the chart for the exact dimensions of the refrigerator.
- 3. IMPORTANT! Calculate the minimum opening required. When installing next to cabinets, you must allow for Door Edge Clearance. (Multiply Door Edge Clearance by 2 for counter-depth models.) When installing next to a wall, you must allow for

4. Calculate how much the refrigerator will protrude from cabinetry. If the result is undesired, consider a counter-depth model.

"C" - 24* Cabinet Depth + approx. 2* Electric and Water Connection

Clearances = ____ which will Protrude Past Cabinets

5. Measure each door and entry way in the home leading to the kitchen to ensure the refrigerator can be moved through.

